BUILT TOUGH, EASY TO SERVICE

STRIKE FIRST
FIRE EXTINGUISHERS

WHEN SECONDS COUNT.

Manufacturing Fire Equipment for over 35 Years

info@strike-first.com | strike-first.com

MULTI-PURPOSE

ABC DRY CHEMICAL

6 YEAR WARRANTY | A | B | C

- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)
- 90% MAP (mono ammonium phosphate powder)

LISTED HOMOLOGUÉ — **MEETS OR EXCEEDS** CAN/ULC-S504 & S508

LISTED — **MEETS OR EXCEEDS** ANSI/UL 299 & 711

CAPACITY	2.5 lbs (1.13 kg)	5 lbs (2.3 kg)	5 lbs (2.3 kg)	10 lbs (4.5 kg)	20 lbs (9.1 kg)	30 lbs (13.6 kg)
Model No.	SF-ABC110ST	SF-ABC310	SF-ABC340	SF-ABC680	SF-ABC1020	SF-ABC30
UL/ULC Rating	1-A : 10-B : C	3-A : 10-B : C	3-A : 40-B : C	6-A : 80-B : C	10-A : 120-B : C	10-A : 120-B : C

REGULAR

BC DRY CHEMICAL

6 YEAR WARRANTY | B | C

- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)

CAPACITY	2.75 lbs (1.2 kg)	5 lbs (2.3 kg)	10 lbs (4.5 kg)	20 lbs (9.1 kg)
Model No.	SF-SB275	SF-SB5	SF-SB10	SF-SB20
UL/ULC Rating	10-B : C	10-B : C	60-B : C	80-B : C

LISTED — **MEETS OR EXCEEDS** ANSI/UL 299 & 711

LISTED HOMOLOGUÉ — **MEETS OR EXCEEDS** CAN/ULC-S504 & S508

FIRE EXTINGUISHER CLASS LEGEND:

A WOOD, PAPER, CLOTH | B FLAMMABLE LIQUIDS & GASES | C ELECTRICAL EQUIPMENT | K RESTAURANT, KITCHEN HAZARD

CO_2 CARBON DIOXIDE

5 YEAR WARRANTY | B | C

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin and retaining chain
- Chrome plated solid brass valve
- Strong impact resistant horn
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- D.O.T. approved cylinder
- U.S.C.G. approved with bracket listed on label
- Temperature range: -22°F to 120°F (-30°C to 49°C)

CAPACITY	5 lbs (2.3 kg)	10 lbs (4.5 kg)	15 lbs (6.8 kg)	20 lbs (9.1 kg)
Model No.	SF-5C02	SF-10C02	SF-15C02	SF-20C02
UL/ULC Rating	5-B : C	10-B : C	10-B : C	10-B : C

UL LISTED — MEETS OR EXCEEDS ANSI/UL 154 & 711

ULC LISTED HOMOLOGUÉ — MEETS OR EXCEEDS CAN/ULC-S503 & S508

WATER

5 YEAR WARRANTY | A

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar-coded labels for accurate service
- Shipped empty without pressure
- Schrader valve for pressurizing
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 40°F to 120°F (4°C to 49°C)

CAPACITY	2.4 gallons (9 litres)
Model No.	SF-PW250
UL/ULC Rating	2-A

UL LISTED — MEETS OR EXCEEDS ANSI/UL 299 & 711

ULC LISTED HOMOLOGUÉ — MEETS OR EXCEEDS CAN/ULC-S504 & S508

FIRE EXTINGUISHER CLASS LEGEND:

A WOOD, PAPER, CLOTH | B FLAMMABLE LIQUIDS & GASES | C ELECTRICAL EQUIPMENT | K RESTAURANT, KITCHEN HAZARD

WATER MIST

5 YEAR WARRANTY | A | C

- Stainless steel cylinder powder coat white
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- QR and bar-coded labels for accurate service
- Shipped empty without pressure
- MR Conditional Approval: 7-Tesla or less
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 40°F to 120°F (4°C to 49°C)

CAPACITY	2.4 gallons (9 litres)
Model No.	SF-WM250
UL/ULC Rating	2-A : C

LISTED
MEETS OR EXCEEDS ANSI/UL 8 & 711

LISTED HOMOLOGUÉ
MEETS OR EXCEEDS CAN/ULC-S554 & S508

WET CHEMICAL

5 YEAR WARRANTY | A | K

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar-coded labels for accurate service
- Factory filled and pressurized
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 35°F to 120°F (2°C to 49°C)

CAPACITY	1.6 gallons (6 litres)
Model No.	SF-6LK
UL/ULC Rating	1-A : K

LISTED
MEETS OR EXCEEDS ANSI/UL 299 & 711

LISTED HOMOLOGUÉ
MEETS OR EXCEEDS CAN/ULC-S504 & S508

FIRE EXTINGUISHER CLASS LEGEND:

A WOOD, PAPER, CLOTH

B FLAMMABLE LIQUIDS & GASES

C ELECTRICAL EQUIPMENT

K RESTAURANT, KITCHEN HAZARD

DRY CHEMICAL

AUTOMATIC HEAT ACTUATED MULTI-PURPOSE

A B C

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- UL Listed Heat Activated Sprinkler Head, rated at 165 degrees F (74° Celsius)
- Meets D.O.T. Requirements
- Designed to provide supplementary fire protection
- Available in two mounting styles: horizontal and vertical
- Disposable unit, does not require maintenance and inspection at 6 or 12 years
- Typical installation locations: specific fire risk areas such as flammable liquid storage rooms, construction trailers and manufacturing process areas i.e. paint booths

CAPACITY	2.5 lbs (1.13 kg)	5 lbs (2.3 kg)	10 lbs (4.5 kg)	20 lbs (9.1 kg)
Model No.	SF-AFE2.5ABCV	SF-AFE5ABCV	SF-AFE10ABCV	SF-AFE20ABCV
	SF-AFE2.5ABCH	SF-AFE5ABCH	SF-AFE10ABCH	SF-AFE20ABCH

ALL-WEATHER SERIES

PLASTIC CABINETS

- Constructed from high-impact ABS plastic
- Resistant to rust and dents
- UV Resistant
- Screen print of fire extinguisher symbol; white on red, red on white
- Low maintenance, easy to clean
- Available in 3 sizes to accommodate 2.5lb., 5lb., 10lb., and 20lb. dry chemical extinguishers
- Red and white options
- Keyed cylinder lock – 151 keycode
- Extra long wire for hammer use

CAPACITY	5 lbs (2.3 kg)	10 lbs (4.5 kg)	20 lbs (9.1 kg)
Model No.	AW-5-R (Red)	AW-10-R (Red)	AW-20-R (Red)
	AW-5-W (White)	AW-10-W (White)	AW-20-W (White)
Compatible Fire Extinguisher	SF-ABC110ST SF-ABC310 SF-ABC340	SF-ABC680	SF-ABC1020

FIRE EXTINGUISHER CLASS LEGEND:

A WOOD, PAPER, CLOTH

B FLAMMABLE LIQUIDS & GASES

C ELECTRICAL EQUIPMENT

K RESTAURANT, KITCHEN HAZARD

FIRE EXTINGUISHER

VEHICLE/MARINE BRACKETS

STANDARD DUTY

MODEL	UP2, UP2 – DB	UB5, UB5 – DB
For Extinguisher	2.5 lb Dry Chemical	5 lb Dry Chemical
U.S.C.G. Approved	YES	YES

- Durable polyester powder paint finish
- Stainless steel strap and clips
- Durable rubber bumpers

MEDIUM DUTY

MODEL	UP10 – MD	UP5 – MD
Diameter	5 1/8" (13 cm)	4 1/4" (11 cm)
For Extinguisher	10 lb Dry Chemical	5 lb Dry Chemical
U.S.C.G. Approved	YES	YES

- Durable polyester powder paint finish
- Heavy gauge steel construction
- Compact design
- Ideal for forklifts, industrial trucks and delivery vehicles
- Double Strap Available

HEAVY DUTY

MODEL	HDVB-1	HDVB-2	HDVB-3	HDVB-4
Diameter	4 – 4 3/4" (10 – 12 cm)	5 – 6" (13 – 15 cm)	6 1/4 – 7 1/8" (16 – 18 cm)	6 1/4 – 7 1/8" (16 – 18 cm)
For Extinguisher	5 lb ABC/BC	10 lb ABC/BC	20 lb ABC/BC	30 lb ABC
		5 lb CO_2	10 lb CO_2 15 lb CO_2	
U.S.C.G. Approved	YES	YES	YES	YES

- Strong Uni-Body Construction
- Reflective label for added safety
- Stainless steel pull pin with tether
- Rounded corners for added safety
- Durable polyester powder coat finish
- Individually boxed for easy handling

WALL HOOKS

TYPE	PART NO.	FOR MODEL(S)
Dry Chemical	C160739	5 lb ABC/BC
	C160753	10 lb ABC/BC
	C160793	20 lb ABC/BC
	C160794	30 lb ABC/BC
CO_2	SF5WH	5 lb CO_2
	SF1015WH	10 lb CO_2
		15 lb CO_2
	SF20WH	20 lb CO_2
Class K Water	W160600	1.6 gal (6L) Class K
		2.4 gal (9L) Water

- Heavy gauge steel construction
- Designed for easy removal of fire extinguisher
- Durable polyester powder coat finish
- Universal design

EXTINGUISHER CART

MODEL	CAPACITY	HEIGHT	WIDTH	DEPTH	WEIGHT
HD-CART	7 – 8" (18 – 20 cm) Diameter	39" (99 cm)	13 1/4" (34 cm)	13 1/2" (34 cm)	20 lb (9 kg)

Shown with 30 lb ABC

STRIKE FIRST FIRE EXTINGUISHERS

777 Tapscott Road
Scarborough
Ontario, Canada M1X 1A2

P 416 299-7767 TF 1 888 575-1132

info@strike-first.com | www.strike-first.com